
MySQL++ User Manual

Kevin Atkinson
Sinisa Miliojevic
Monty Widenius
Warren Young

Copyright © 1998-2001, 2005 Kevin AtkinsonMySQL AB Educational Technology Resources
\$Date: 2005-04-30 06:52:56 -0600 (Sat, 30 Apr 2005) \$

Table of Contents

1. Introduction	1
2. Overview	1
2.1. The Connection Object	2
2.2. The Query Object	2
2.3. Result Sets	2
2.4. Exceptions	3
3. Tutorial	3
3.1. Running the Examples	3
3.2. The Basics	4
3.3. Specialized SQL Structures	8
3.4. Which Query Type to Use?	13
3.5. Let's Do Something Useful	14
4. Template Queries	17
4.1. Setting up template queries	19
4.2. Setting the parameters at execution time	20
4.3. Using defaults	20
4.4. Combining the two	21
4.5. Error Handling	21
5. Specialized SQL Structures	21
5.1. sql_create	22
5.2. sql_create with Compare	22
5.3. sql_create with Additional Initializers	23
5.4. Additional Features of Specialized SQL Structures	24
5.5. alternate creation methods	24
5.6. expanding ssqls macros	25
5.7. Extending the SSQLS Mechanism	25
6. Licensing	25
6.1. GNU Lesser General Public License	25

1. Introduction

MySQL++ is a powerful C++ wrapper for MySQL's C API. Its purpose is to make working with queries as easy as working with STL containers.

The latest version of MySQL++ can be found at the official web site [<http://tangentsoft.net/mysql++/>].

Support for MySQL++ can be had on the mailing list [<http://lists.mysql.com/plusplus>]. That page hosts the mailing list archives, and tells you how you can subscribe.

2. Overview

MySQL++ has developed into a very complex and powerful library, with many different ways to accomplish the

same task. Unfortunately, this means that figuring out how to perform a simple task can be frustrating for new users. In this section we will provide an overview of the most important user-facing components of the library.

The overall process for using MySQL++ is similar to that of most other database access APIs:

1. Open the connection
2. Form and execute the query
3. Iterate through the result set
4. Go to 2 :)

There is, however, a lot of extra functionality along each step of the way.

2.1. The Connection Object

A Connection [[../refman/html/classmysqlpp_1_1Connection.html](#)] object manages the connection to the MySQL server. You need at least one of these objects to do anything. A Connection object can either create Query objects for you, or you can execute queries directly through the Connection object. The separate Query object is the recommended way as it gives you far more power.

2.2. The Query Object

A Query [[../refman/html/classmysqlpp_1_1Query.html](#)] object is the recommended way of building and executing queries. It is subclassed from `std::stringstream` which means you can write to it like any other C++ stream to form a query. The library includes stream manipulators [[../refman/html/manip_8h.html](#)] that make it easy to generate syntactically-correct SQL.

You can also set up template queries with this class. Template queries work something like the C `printf()` function: you set up a fixed query string with tags inside that indicate where to insert the variable parts. If you have multiple queries that are structurally similar, you simply set up one template query, and use that in the various locations of your program.

A third method for building queries is to use Specialized SQL Structures (SSQLS). This feature presents your results as a C++ data structure, instead of making you access the data through MySQL++ intermediary classes. It also reduces the amount of embedded SQL code your program needs.

2.3. Result Sets

The actual data elements in a result set are stored in a special `std::string`-like class. Objects of this class can automatically convert themselves to any of the basic C data types as well as some additional MySQL++-specific types that are designed to handle those MySQL that don't map well onto the basic C types. For instance, you can convert a MySQL `DATETIME` field to a MySQL++ `DateTime` [[../refman/html/structmysqlpp_1_1DateTime.html](#)] object automatically. If there is a problem in the conversion it will either set a warning flag or throw an exception, depending on how you set the library up.

MySQL++ has a number of different ways of representing query results.

Queries That Do Not Return Data

Not all SQL queries return data. An example is `CREATE TABLE`. For these types of queries, there is a special result type [[../refman/html/classmysqlpp_1_1ResNSel.html](#)] that simply reports the state resulting from the query: whether the query was successful, how many rows it impacted (if any), etc.

Queries That Return Data: Dynamic Method

The easiest way to retrieve data from MySQL uses a Result [../refman/html/classmysqlpp_1_1Result.html] object, which includes one or more Row [../refman/html/classmysqlpp_1_1Row.html] objects. Because these classes are `std::vector`-like containers, you can treat the result set as a two-dimensional array. For example you can get the 5th item on the 2nd row by simply saying `result[1][4]`. You can also access row elements by field name, like this: `result[2].lookup_by_name("price")`.

An alternate way of accessing your query results is through a ResUse [../refman/html/classmysqlpp_1_1ResUse.html] object. This class acts more like an STL input iterator than a container: you walk through your result set one item at a time, always going forward. You can't seek around in the result set, and you can't know how many results are in the set until you find the end. This method is more efficient when there can be arbitrarily many results, which could pose a memory allocation problem with the previous technique.

Queries That Return Data: Static Method

The Specialized SQL Structures (SSQLS) feature method above defines C++ structures that match the table structures in your database schema.

We call it the "static" method because the table structure is fixed at compile time; if you change the database schema, you have to change your SSQLS definitions and recompile. If you fail to do this, your program will throw an exception when you try to stuff a result set into an outdated data structure.

The advantage of this method is that your program will require very little embedded SQL code. You can simply execute a query, and receive your results as C++ data structures, which can be accessed just as you would any other structure. The results can be accessed through the Row object, or you can ask the library to dump the results into a sequential or set-associative STL container for you. Consider this:

```
vector<mystruct> v;
Query q = connection.query();
q << "SELECT * FROM mytable";
q.storein(v);
for (vector<mystruct>::iterator it = v.begin(); it != v.end(); ++v) {
    cout << "Price: " << v.price << endl;
}
```

Isn't that slick?

2.4. Exceptions

By default, the library throws exceptions [../refman/html/exceptions_8h.html] derived from `std::exception` whenever it encounters an error. You can ask the library to set an error flag instead, if you like, but the exceptions carry more information. Not only do they include a string member telling you why the exception was thrown, there are several exception types, so you can distinguish between several types of error within a single `try` block.

3. Tutorial

This tutorial is meant to give you a jump start in using MySQL++. While it is a very complicated and powerful library, it's possible to make quite functional programs without tapping but a fraction of its power. This section will introduce you to the most useful fraction.

This tutorial assumes you know C++ fairly well, in particular the Standard Template Library (STL) and exceptions.

3.1. Running the Examples

All of the examples are complete running programs. They may or may not be built for you already, depending on how you installed the library.

If you installed MySQL++ from the source tarball on a Unixy system, the examples should have been built along with the library. If not, simply go into the examples directory and type `make`.

If you installed the library via RPM, the examples are in the `mysql++-devel` RPM. After installing that, the examples are in `/usr/src/mysql++/examples`. To build them, go into that directory and type `make -f Makefile.simple`. See the file `/usr/share/doc/mysql++-devel*/README.examples` for more details.

If you are on a Windows system, the build process for the library should have built the examples as well. Where the programs are depends on which compiler you're using. There should be a `README.*` file in the distribution specific to your compiler with further instructions.

Once you have the examples building, you need to initialize the sample database by running the `resetdb` example. The usage of `resetdb` is as follows:

```
resetdb [host [user [password [port]]]]
```

If you leave off `host`, `localhost` is assumed. If you leave off `user`, your current username is assumed. If you leave off the `password`, it is assumed that you don't need one. And if you leave off the `port`, it will use the standard MySQL port number.

The user you give `resetdb` needs to be an account with permission to create databases. Once the database is created you can use any account that has full permission to the sample database `mysql_cpp_data`.

You may also have to re-run `resetdb` after running some of the other examples, as they change the database.

3.2. The Basics

A simple example

The following example demonstrates how to open a connection, execute a simple query, and display the results. The code can be found in the file `examples/simple1.cpp`. Note that, like most of the other examples, it requires the common routines in `examples/util.cpp`; you can't build it directly.

```
#include "util.h"
#include <mysql++.h>
#include <iostream>
#include <iomanip>

using namespace std;

int
main(int argc, char *argv[])
{
    try {
        // Connect to the sample database
        mysqlpp::Connection con(mysqlpp::use_exceptions);
        if (!connect_to_db(argc, argv, con)) {
            return 1;
        }

        // Create a query object that is bound to con.
        mysqlpp::Query query = con.query();

        // Print out the stock table
        print_stock_table(query);
    }
    catch (mysqlpp::BadQuery& er) {
        // handle any connection or query errors that may come up
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
}
```

```
    catch (mysqlpp::BadConversion& er) {
        // handle bad conversions
        cerr << "Error: " << er.what() << "\n." << endl
            << "retrieved data size: " << er.retrieved
            << " actual data size: " << er.actual_size << endl;
        return -1;
    }
    catch (exception & er) {
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
    return 0;
}
```

Everything here should be fairly obvious. Take particular notice of how we used an iterator with the result set.

A slightly more complicated example

This example is almost like the previous one, except that it uses exceptions and the automatic conversion feature of ColData. Pay particular notice to how exceptions are used. This is `examples/complic1.cpp`:

```
#include "util.h"
#include <mysql++.h>
#include <iostream>
#include <iomanip>

using namespace std;
using namespace mysqlpp;

int
main(int argc, char *argv[])
{
    try {
        Connection con(use_exceptions);
        if (!connect_to_db(argc, argv, con)) {
            return 1;
        }

        Query query = con.query();

        query << "select * from stock";
        cout << "Query: " << query.preview() << endl;

        Result res = query.store();
        cout << "Records Found: " << res.size() << endl << endl;

        Row row;
        cout.setf(ios::left);
        cout << setw(17) << "Item" <<
            setw(4) << "Num" <<
            setw(7) << "Weight" <<
            setw(7) << "Price" << "Date" << endl << endl;

        Result::iterator i;

        cout.precision(3);
        for (i = res.begin(); i != res.end(); i++) {
            row = *i;
            // Regarding the casts to double, we do this so that we can
            // set the display precision. ColData has the nice feature
            // that it will convert to any of the basic C++ types. If
            // there is a problem in the conversion it will throw an
            // exception (caught below). To test it, try changing the
            // row[2] to row[0] below.
```

```
    cout << setw(17) << row.lookup_by_name("ITEM") <<
        setw(4) << row[1] <<
        setw(7) << double(row[2]) <<
        setw(7) << double(row[3]);

    // The ColData is implicitly converted to a date here.
    Date date = row.lookup_by_name("SDATE");
    cout.setf(ios::right);
    cout.fill('0');
    cout << setw(2) << date.month << "-" << setw(2) <<
        date.day << endl;
    cout.fill(' ');
    cout.unsetf(ios::right);
}

return 0;
}
catch (BadQuery& er) {
    // Handle any connection or query errors that may come up
    cerr << "Error: " << er.what() << endl;
    return -1;
}
catch (BadConversion& er) {
    // Handle bad conversions
    cerr << "Error: " << er.what() << "\",." << endl
        << "retrieved data size: " << er.retrieved
        << " actual data size: " << er.actual_size << endl;
    return -1;
}
catch (exception& er) {
    cerr << "Error: " << er.what() << endl;
    return -1;
}
}
```

Notes on exceptions

Everything should be fairly obvious. A few notes about exceptions, however:

1. When the `use_exceptions` flag is set for a parent object it is also set for all of the children it creates after the flag is set. For example when the `use_exceptions` flag is set for the `con` object, it is also set for the `query` object. Please note that the `use_exceptions` flag is not linked, it is copied. This means that when you change the `use_exceptions` flag only its new children are affected, not the ones it already created.
2. `ColData` will always throw an exception [[../refman/html/classmysqlpp_1_1BadConversion.html](http://refman/html/classmysqlpp_1_1BadConversion.html)] when it is unable to do a requested conversion. A bad conversion is defined as one where: a) all the characters from the string are not yet processed, and b) the remaining characters are something other than whitespace, zeros (0), or periods (.). This means that an exception is thrown when `1.25` is converted into an int, but not when `1.00` is converted into an int. In the latter case, MySQL++ knows that it can safely throw away the fractional part.

To see how the exceptions work, try creating an error. Some good things to try would be misspelling the table name or changing the double to an int.

Getting info about the fields

The following example demonstrates how to get some basic information about the fields, including the name of the field and the SQL type. This is `examples/fieldinf1.cpp`:

```
#include "util.h"
#include <mysql++.h>
```

```

#include <iostream>
#include <iomanip>

using namespace std;
using namespace mysqlpp;

int
main(int argc, char *argv[])
{
    try {
        Connection con(use_exceptions);
        if (!connect_to_db(argc, argv, con)) {
            return 1;
        }

        Query query = con.query();
        query << "select * from stock";
        cout << "Query: " << query.preview() << endl;

        Result res = query.store();
        cout << "Records Found: " << res.size() << endl << endl;

        cout << "Query Info:\n";
        cout.setf(ios::left);

        for (unsigned int i = 0; i < res.names().size(); i++) {
            cout << setw(2) << i
                // this is the name of the field
                << setw(15) << res.names(i).c_str()
                // this is the SQL identifier name
                // Result::types(unsigned int) returns a mysql_type_info which in many
                // ways is like type_info except that it has additional sql type
                // information in it. (with one of the methods being sql_name())
                << setw(15) << res.types(i).sql_name()
                // this is the C++ identifier name which most closely resembles
                // the sql name (its implementation defined and often not very readable)
                << setw(20) << res.types(i).name()
                << endl;
        }

        cout << endl;

        if (res.types(0) == typeid(string)) {
            // this is demonstrating how a mysql_type_info can be
            // compared with a C++ type_info.
            cout << "Field 'item' is of an SQL type which most "
                "closely resembles\nthe C++ string type\n";
        }

        if (res.types(1) == typeid(longlong)) {
            cout << "Field 'num' is of an SQL type which most "
                "closely resembles\nC++ long long int type\n";
        }
        else if (res.types(1).base_type() == typeid(longlong)) {
            // you have to be careful as if it can be null the actual
            // type is Null<TYPE> not TYPE. So you should always use
            // the base_type method to get at the underlying type.
            // If the type is not null than this base type would be
            // the same as its type.
            cout << "Field 'num' base type is of an SQL type which "
                "most closely\nresembles the C++ long long int type\n";
        }

        return 0;
    }
    catch (BadQuery& er) {
        // handle any connection or query errors that may come up
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
}

```

```
    catch (BadConversion& er) {
        // handle bad conversions
        cerr << "Error: " << er.what() << "\n." << endl
            << "retrieved data size: " << er.retrieved
            << " actual data size: " << er.actual_size << endl;
        return -1;
    }
    catch (exception& er) {
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
}
```

3.3. Specialized SQL Structures

Retrieving data

The next example introduces one of the most powerful features of MySQL++: Specialized SQL Structures (SSQLS). This is examples/custom1.cpp:

```
#include "util.h"

#include <mysql++.h>
#include <custom.h>

#include <iostream>
#include <iomanip>
#include <vector>

using namespace std;
using namespace mysqlpp;

sql_create_5(stock,          // struct name,
             1, 5,          // I'll explain these latter
             string, item,  // type, id
             longlong, num,
             double, weight,
             double, price,
             Date, sdate)

// this is calling a very complex macro which will create a custom
// struct "stock" which has the variables:
//   string item
//   int num
//   ...
//   Date sdate
// defined as well methods to help populate the class from a mysql row
// among other things that I'll get too in a latter example
int
main(int argc, char *argv[])
{
    try {
        // its in one big try block
        Connection con(use_exceptions);
        if (!connect_to_db(argc, argv, con)) {
            return 1;
        }

        Query query = con.query();
        query << "select * from stock";

        vector < stock > res;
        query.storein(res);
        // this is storing the results into a vector of the custom struct
        // "stock" which was created my the macro above.
    }
```

```
cout.setf(ios::left);
cout << setw(17) << "Item"
    << setw(4) << "Num"
    << setw(7) << "Weight"
    << setw(7) << "Price" << "Date" << endl << endl;

// Now we we iterate through the vector using an iterator and
// produce output similar to that using Row
// Notice how we call the actual variables in i and not an index
// offset. This is because the macro at the begging of the file
// set up an *actual* struct of type stock which contains the
// variables item, num, weight, price, and data.

cout.precision(3);
vector<stock>::iterator i;
for (i = res.begin(); i != res.end(); i++) {
    cout << setw(17) << i->item.c_str()
        // unfortunately the gnu string class does not respond to format
        // modifiers so I have to convert it to a const char *.
        << setw(4) << i->num
        << setw(7) << i->weight
        << setw(7) << i->price << i->sdate << endl;
    }
    return 0;
}
}
catch (BadQuery& er) {
    // handle any connection or query errors that may come up
    cerr << "Error: " << er.what() << endl;
    return -1;
}
catch (BadConversion& er) {
    // handle bad conversions
    cerr << "Error: " << er.what() << "\"." << endl
        << "retrieved data size: " << er.retrieved
        << " actual data size: " << er.actual_size << endl;
    return -1;
}
catch (exception & er) {
    cerr << "Error: " << er.what() << endl;
    return -1;
}
}
```

As you can see, SSQLS is very powerful.

Adding data

SSQLS can also be used to add data to a table. This is examples/custom2.cpp:

```
#include "util.h"

#include <mysql++.h>
#include <custom.h>

#include <iostream>
#include <string>
#include <vector>

using namespace std;
using namespace mysqlpp;

sql_create_5(stock,
            1, 5,
            string, item,
            longlong, num,
            double, weight,
```

```
        double, price,
        Date, sdate)

int
main(int argc, char *argv[])
{
    try {
        Connection con(use_exceptions);
        if (!connect_to_db(argc, argv, con)) {
            return 1;
        }

        Query query = con.query();

        // create an empty stock object
        stock row;

        // populate stock
        row.set("Hot Dogs", 100, 1.5, 1.75, "1998-09-25");

        // form the query to insert the row
        // the table name is the name of the struct by default
        query.insert(row);

        // show the query about to be executed
        cout << "Query : " << query.preview() << endl;

        // execute a query that does not return a result set
        query.execute();

        // now print the new table;
        print_stock_table(query);
    }
    catch (BadQuery& er) {
        // handle any connection or query errors that may come up
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
    catch (BadConversion& er) {
        // handle bad conversions
        cerr << "Error: " << er.what() << "\"." << endl
            << "retrieved data size: " << er.retrieved
            << " actual data size: " << er.actual_size << endl;
        return -1;
    }
    catch (exception& er) {
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
    return 0;
}
```

That's all there is to it. Because this example modifies the data you should run `resetdb` after running the example code.

Modifying data

It almost as easy to modify data with `SSQLS`. This is `examples/custom3.cpp`:

```
#include "util.h"

#include <mysql++.h>
#include <custom.h>
```

```
#include <iostream>
#include <string>
#include <vector>

using namespace std;
using namespace mysqlpp;

sql_create_5(stock,
            1, 5,
            string, item,
            longlong, num,
            double, weight,
            double, price,
            Date, sdate)

int
main(int argc, char *argv[])
{
    try {
        Connection con(use_exceptions);
        if (!connect_to_db(argc, argv, con)) {
            return 1;
        }

        Query query = con.query();
        query << "select * from stock where item = \"Nürnbergger Brats\"";

        // Is the query was successful? If not throw a bad query.
        Result res = query.store();
        if (res.empty()) {
            throw BadQuery("UTF-8 bratwurst item not found in "
                           "table, run resetdb");
        }

        // Because there should only be one row in the result set, we
        // don't need to use a vector. Just store the first row
        // directly in "row". We can do this because one of the
        // constructors for stock takes a Row as a parameter.
        stock row = res[0];

        // Create a copy so that the replace query knows what the
        // original values are.
        stock row2 = row;

        // Change item column to use only 7-bit ASCII, and to
        // deliberately be wider than normal column widths printed by
        // print_stock_table().
        row.item = "Nuerenberger Bratwurst";

        // Form the query to replace the row. The table name is the
        // name of the struct by default.
        query.update(row2, row);

        // Show the query about to be executed.
        cout << "Query : " << query.preview() << endl;

        // Call execute(), since the query won't return a result set.
        query.execute();

        // Now print the new table
        print_stock_table(query);
    }
    catch (BadQuery& er) {
        // handle any connection or query errors that may come up
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
    catch (BadConversion& er) {
        // handle bad conversions
        cerr << "Error: " << er.what() << "\n." << endl
    }
}
```

```
        << "retrieved data size: " << er.retrieved
        << " actual data size: " << er.actual_size << endl;
    return -1;
}
catch (exception& er) {
    cerr << "Error: " << er.what() << endl;
    return -1;
}
return 0;
}
```

When you run the example you will notice that in the WHERE clause only the 'item' field is checked for. This is because SSQLS also also less-than-comparable.

Don't forget to run resetdb after running the example.

Less-than-comparable

SSQLS structures can be sorted and stored in STL associative containers as demonstrated in the next example. This is custom4.cpp:

```
#include "util.h"

#include <mysql++.h>
#include <custom.h>

#include <iostream>
#include <iomanip>
#include <string>
#include <vector>

using namespace std;
using namespace mysqlpp;

sql_create_5(stock,
    1, // This number is used to make a SSQLS less-than-comparable.
      // When comparing two SSQLS structures, the first N elements are
      // compared. In this instance, we are saying that we only want
      // the first element ('item') to be used when comparing two
      // stock structures.

    5, // Each SSQLS structure includes a number of constructors. Some
      // of these are fixed in nature, but one of these will have this
      // number of arguments, one for each of the first N elements in
      // the structure; it is an initialization ctor. Since N is the
      // same as the number of structure elements in this instance,
      // that ctor will be able to fully initialize the structure. This
      // behavior is not always wanted, however, so the macro allows
      // you make the constructor take fewer parameters, leaving the
      // remaining elements uninitialized. An example of when this is
      // necessary is when you have a structure containing only two
      // integer elements: one of the other ctors defined for SSQLS
      // structures takes two ints, so the compiler barfs if you pass
      // 2 for this argument. You would need to pass 0 here to get
      // that SSQLS structure to compile.
    string, item,
    longlong, num,
    double, weight,
    double, price,
    Date, sdate)

int
main(int argc, char *argv[])
{
```

```

try {
    Connection con(use_exceptions);
    if (!connect_to_db(argc, argv, con)) {
        return 1;
    }

    Query query = con.query();

    query << "select * from stock";

    // here we are storing the elements in a set not a vector.
    set <stock> res;
    query.storein(res);

    cout.setf(ios::left);
    cout << setw(17) << "Item"
         << setw(4) << "Num"
         << setw(7) << "Weight"
         << setw(7) << "Price" << "Date" << endl << endl;

    // Now we iterate through the set. Since it is a set the list will
    // naturally be in order.
    set<stock>::iterator i;
    cout.precision(3);
    for (i = res.begin(); i != res.end(); ++i) {
        cout << setw(17) << i->item.c_str()
             << setw(4) << i->num
             << setw(7) << i->weight
             << setw(7) << i->price << i->sdate << endl;
    }

    i = res.find(stock("Hamburger Buns"));
    if (i != res.end()) {
        cout << "Hamburger Buns found. Currently " << i->num <<
             " in stock.\n";
    }
    else {
        cout << "Sorry no Hamburger Buns found in stock\n";
    }

    // Now we are using the set's find method to find out how many
    // Hamburger Buns are in stock.

    return 0;
}
catch (BadQuery& er) {
    // handle any connection or query errors that may come up
    cerr << "Error: " << er.what() << endl;
    return -1;
}
catch (BadConversion& er) {
    // handle bad conversions
    cerr << "Error: " << er.what() << "\n." << endl
         << "retrieved data size: " << er.retrieved
         << " actual data size: " << er.actual_size << endl;
    return -1;
}
catch (exception& er) {
    cerr << "Error: " << er.what() << endl;
    return -1;
}

return 0;
}

```

3.4. Which Query Type to Use?

There are three major ways to execute a query in MySQL++: `Query::execute()`, `Query::store()`, and `Query::use()`. Which should you use, and why?

`execute()` is for queries that do not return data *per se*. For instance, `CREATE INDEX`. You do get back some information from the MySQL server, which `execute()` returns to its caller in a `ResNSel` [../refman/html/classmysqlpp_1_1ResNSel.html] object. In addition to the obvious — a flag stating whether the query succeeded or not — this object also contains things like the number of rows that the query affected. If you only need the success status, there's `Query::exec()`, which just returns `bool`.

If your query does pull data from the database, the simplest option is `store()`. This returns a `Result` [../refman/html/classmysqlpp_1_1Result.html] object, which contains an in-memory copy of the result set. The nice thing about this is that `Result` is a sequential container, like `std::vector`, so you can iterate through it forwards and backwards, access elements with subscript notation, etc. There are also the `storein()` methods, which actually put the result set into an STL container of your choice. The downside of these methods is that a sufficiently large result set will give your program memory problems.

For these large result sets, you should use the `use()` method instead. This returns a `ResUse` [../refman/html/classmysqlpp_1_1ResUse.html] object, which is similar to `Result`, but without all of the random-access features. This is because a "use" query tells the database server to send the results back one row at a time, to be processed linearly. It's analogous to a C++ stream's input iterator, as opposed to a random-access iterator that a container like `vector` offers. By accepting this limitation, you can process arbitrarily large result sets.

3.5. Let's Do Something Useful

These next few examples demonstrate just how powerful C++ can be, allowing you to do a lot of work in few lines of code without losing efficiency.

Since the code is meant to be re-used as-is, constants that can differ from one case to another have been grouped in order to simplify editing. Also, all of these examples have full error checking code, showing off the power of MySQL++'s exception handling features.

Loading binary file in a BLOB column

Since MySQL 3.23, BLOB columns have been available, but their use is sometimes not straightforward. Besides showing how easy it can be with MySQL++, this example demonstrates several features of MySQL++. The program requires one command line parameter, which is a full path to the binary file. This is `examples/load_file.cpp`:

```
#include <mysql++.h>
#include <sys/stat.h>
#include <fstream>
#include <errno.h>
#include <stdlib.h>

using namespace std;
using namespace mysqlpp;

const char MY_DATABASE[] = "telcent";
const char MY_TABLE[] = "fax";
const char MY_HOST[] = "localhost";
const char MY_USER[] = "root";
const char MY_PASSWORD[] = "";
const char MY_FIELD[] = "fax"; // BLOB field

int
main(int argc, char *argv[])
{
    if (argc < 2) {
        cerr << "Usage : load_file full_file_path" << endl << endl;
        return -1;
    }
}
```

```

}
Connection con(use_exceptions);
try {
    con.real_connect(MY_DATABASE, MY_HOST, MY_USER, MY_PASSWORD, 3306,
                    0, 60, NULL);
    Query query = con.query();
    ostringstream strbuf;
    ifstream In(argv[1], ios::in | ios::binary);
    struct stat for_len;
    if ((In.rdbuf()->is_open()) {
        if (stat(argv[1], &for_len) == -1)
            return -1;
        unsigned int blen = for_len.st_size;
        if (!blen)
            return -1;
        char *read_buffer = new char[blen];
        In.read(read_buffer, blen);
        string fill(read_buffer, blen);
        strbuf << "INSERT INTO " << MY_TABLE << " (" << MY_FIELD <<
            ") VALUES(\"" << mysqlpp::escape << fill << "\"" << ends;
        query.exec(strbuf.str());
        delete[]read_buffer;
    }
    else
        cerr << "Your binary file " << argv[1] <<
            "could not be open, errno = " << errno;
    return 0;
}
catch (BadQuery& er) {
    // handle any connection or query errors that may come up
    cerr << "Error: " << er.what() << " " << con.errnum() << endl;
    return -1;
}
catch (BadConversion& er) {
    // handle bad conversions
    cerr << "Error: " << er.what() << "\"." << endl
        << "retrieved data size: " << er.retrieved
        << " actual data size: " << er.actual_size << endl;
    return -1;
}
catch (exception& er) {
    cerr << "Error: " << er.what() << endl;
    return -1;
}
}

```

One of the features of this example is the use of the escape manipulator [[../refman/html/namespacemysqlpp.html#escape_manip](#)]. Although the library does have automatic quoting and escaping, it is only supported for ColData, as that class contains the necessary type information. Rather than force MySQL++ to scan the string to determine whether quoting and escaping is necessary, it was decided to leave the choice of quoting and escaping to the user for all other types.

Displaying images in HTML from BLOB column

This example is also a very short one, considering the function that it performs. Although all modern versions of MySQL have a command that dumps data from BLOB column to a binary file, this example shows how to do it in your code instead, without requiring an temporary file on disk. This is `examples/cgi_image.cpp`:

```

#include <mysql++.h>

using namespace std;
using namespace mysqlpp;

```

```

#define MY_DATABASE "telcent"
#define MY_TABLE    "fax"
#define MY_HOST     "localhost"
#define MY_USER     "root"
#define MY_PASSWORD ""
#define MY_FIELD    "fax"          // BLOB field
#define MY_KEY      "datet"       // PRIMARY KEY

int
main(int argc, char *argv[])
{
    if (argc < 2) {
        cerr << "Usage : cgi_image primary_key_value" << endl << endl;
        return -1;
    }

    cout << "Content-type: image/jpeg" << endl;
    Connection con(use_exceptions);
    try {
        con.real_connect(MY_DATABASE, MY_HOST, MY_USER, MY_PASSWORD, 3306,
                        0, 60, NULL);
        Query query = con.query();
        query << "SELECT " << MY_FIELD << " FROM " << MY_TABLE << " WHERE "
              << MY_KEY << " = " << argv[1];
        ResUse res = query.use();
        Row row = res.fetch_row();
        long unsigned int *jj = res.fetch_lengths();
        cout << "Content-length: " << *jj << endl << endl;
        fwrite(row.raw_data(0), 1, *jj, stdout);
        return 0;
    }
    catch (BadQuery& er) {
        cerr << "Error: " << er.what() << " " << con.errnum() << endl;
        return -1;
    }
    catch (exception& er) {
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
}

```

DELETE or UPDATE from SELECT

MySQL's SELECT statement has more power to winnow out just the items of interest from the database than do DELETE or UPDATE. Therefore, many people have wanted the ability to execute a SELECT statement that in fact deletes or updates the rows matched, rather than returning them. This example implements that feature in just a few lines of code. It is examples/updel.cpp:

```

#include <mysql++.h>

#include <string>

using namespace std;
using namespace mysqlpp;

#define MY_DATABASE "telcent"
#define MY_TABLE    "nazivi"
#define MY_HOST     "localhost"
#define MY_USER     "root"
#define MY_PASSWORD ""
#define MY_FIELD    "naziv"
#define MY_QUERY    "SELECT URL from my_table as t1, my_table as t2 where t1.field = t2.field"

int
main()

```

```

{
    Connection con(use_exceptions);
    try {
        ostringstream strbuf;
        unsigned int i = 0;
        con.real_connect(MY_DATABASE, MY_HOST, MY_USER, MY_PASSWORD, 3306,
                        0, 60, NULL);
        Query query = con.query();
        query << MY_QUERY;
        ResUse res = query.use();
        Row row;
        strbuf << "delete from " << MY_TABLE << " where " << MY_FIELD <<
            " in (";
        // for UPDATE just replace the above DELETE FROM with UPDATE statement
        for (; row = res.fetch_row(); i++)
            strbuf << row[0] << ",";
        if (!i)
            return 0;
        string output(strbuf.str());
        output.erase(output.size() - 1, 1);
        output += ")";
        query.exec(output); // cout << output << endl;
        return 0;
    }
    catch (BadQuery& er) {
        // handle any connection or query errors that may come up
        cerr << "Error: " << er.what() << " " << con.errnum() << endl;
        return -1;
    }
    catch (BadConversion& er) {
        cerr << "Error: " << er.what() << "\"." << endl
            << "retrieved data size: " << er.retrieved
            << " actual data size: " << er.actual_size << endl;
        return -1;
    }
    catch (exception& er) {
        cerr << "Error: " << er.what() << endl;
        return -1;
    }
}

```

Notice that the row values used in the IN clause aren't escaped or quoted. This is because row elements are ColData [../refman/html/classmysqlpp_1_1ColData__Tmpl.html] types, so they have automatic escaping and quoting, as appropriate to the type being inserted. If you want to disable this feature, it's easily done: click the ColData link for the details.

Users of this example should beware that one more check is required in order to run this query safely: in some extreme cases, the size of the query might grow larger than MySQL's maximum allowed packet size. This check should be added.

4. Template Queries

Another powerful feature of MySQL++ is being able to set up template queries. These are kind of like C's `printf()` facility: you give MySQL++ a string containing the fixed parts of the query and placeholders for the variable parts, and you can later substitute in values into those placeholders.

The following example demonstrates how to use this feature. This is the program you've run a few times now if you've worked through all the examples, `resetdb.cpp`:

```

#include "util.h"

#include <mysql++.h>

#include <iostream>

```

```

using namespace std;

int
main(int argc, char *argv[])
{
    mysqlpp::Connection con(mysqlpp::use_exceptions);
    try {
        if (!connect_to_db(argc, argv, con, "")) {
            return 1;
        }
    }
    catch (exception& er) {
        cerr << "Connection failed: " << er.what() << endl;
        return 1;
    }

    bool created = false;
    try {
        con.select_db(kpcSampleDatabase);
    }
    catch (mysqlpp::BadQuery &) {
        // Couldn't switch to the sample database, so assume that it
        // doesn't exist and create it.  If that doesn't work, exit
        // with an error.
        if (con.create_db(kpcSampleDatabase)) {
            cerr << "Failed to create sample database: " <<
                con.error() << endl;
            return 1;
        }
        else if (!con.select_db(kpcSampleDatabase)) {
            cerr << "Failed to select sample database." << endl;
            return 1;
        }
        else {
            created = true;
        }
    }

    mysqlpp::Query query = con.query(); // create a new query object

    try {
        query.execute("drop table stock");
    }
    catch (mysqlpp::BadQuery&) {
        // ignore any errors
    }

    try {
        // Send the query to create the table and execute it.
        query << "create table stock (item char(20) not null, num bigint,"
            << "weight double, price double, sdate date)";
        query.execute();

        // Set up the template query to insert the data.  The parse
        // call tells the query object that this is a template and
        // not a literal query string.
        query << "insert into %5:table values (%0q, %1q, %2, %3, %4q)";
        query.parse();

        // This is setting the parameter named table to stock.
        query.def["table"] = "stock";

        // The last parameter "table" is not specified here.  Thus the
        // default value for "table" is used, which is "stock".  Also
        // notice that the first row is a UTF-8 encoded Unicode string!
        // All you have to do to store Unicode data in recent versions
        // of MySQL is use UTF-8 encoding.
        query.execute("Nürnberger Brats", 92, 1.5, 8.79, "2005-03-10");
        query.execute("Pickle Relish", 87, 1.5, 1.75, "1998-09-04");
        query.execute("Hot Mustard", 75, .95, .97, "1998-05-25");
    }
}

```

```

        query.execute("Hotdog Buns", 65, 1.1, 1.1, "1998-04-23");

        if (created) {
            cout << "Created";
        }
        else {
            cout << "Reinitialized";
        }
        cout << " sample database successfully." << endl;
    }
    catch (mysqlpp::BadQuery& er) {
        // Handle any connection or query errors that may come up
        cerr << "Error: " << er.what() << endl;
        return 1;
    }
    catch (mysqlpp::BadConversion& er) {
        // Handle bad conversions
        cerr << "Error: " << er.what() << "\"." << endl
            << "retrieved data size: " << er.retrieved
            << " actual data size: " << er.actual_size << endl;
        return 1;
    }
    catch (exception& er) {
        cerr << "Error: " << er.what() << endl;
        return 1;
    }
}

```

The line just before the call to `query.parse()` sets the template, and the parse call puts it into effect. From that point on, you can re-use this query by calling any of several Query member functions that accept query template parameters. In this example, we're using `Query::execute()`.

Let's dig into this feature a little deeper.

4.1. Setting up template queries

To set up a template query, you simply insert it into the Query object, using numbered placeholders wherever you want to be able to change the query. Then, you call the `parse()` function to tell the Query object that the query string is a template query, and it needs to parse it:

```

query << "select (%2:field1, %3:field2) from stock where
        %1:wheref = %q0:what";
query.parse();

```

The format of the placeholder is:

```
%(modifier)##(:name)(:)
```

Where Modifier can be any one of the following:

%	Print an actual "%"
""	Don't quote or escape no matter what.
q	This will quote and escape the item using the MySQL C API function <code>mysql_escape_string()</code> if it is a string or char *, or another MySQL-specific type that needs to be quoted.
Q	Quote but don't escape based on the same rules as for 'q'. This can save a

	bit of processing time if you know the strings will never need quoting
r	Always quote and escape even if it is a number.
R	Always quote but don't escape even if it is a number.

represents a number up to two digits. It is the order of parameters given to a `SQLQueryParms` [../../refman/html/classmysqlpp_1_1SQLQueryParms.html] object, starting from 0.

":name" is for an optional name which aids in filling `SQLQueryParms`. Name can contain any alpha-numeric characters or the underscore. If you add this, it must start with a letter. If this is not the case, add a colon after the name. If you need to represent an actual colon after the name, follow the name with two colons. The first one will end the name and the second one won't be processed.

4.2. Setting the parameters at execution time

To specify the parameters when you want to execute a query simply use `Query::store(const SQLString &parm0, [..., const SQLString &parm11])`. This type of multiple overload also exists for `Query::use()` and `Query::execute()`. 'parm0' corresponds to the first parameter, etc. You may specify up to 12 parameters. For example:

```
Result res = query.store("Dinner Rolls", "item", "item", "price")
```

with the template query provided above would produce:

```
select (item, price) from stock where item = "Dinner Rolls"
```

The reason we didn't put the template parameters in numeric order...

```
select (%0:field1, %1:field2) from stock where %2:wheref = %q3:what
```

...will become apparent shortly.

4.3. Using defaults

You can also set the parameters one at a time by means of class `Query`'s public data member `def`. To change the values of the `def`, simply use the subscript operator. You can refer to the parameters either by number or by name. The following two examples have the same effect:

```
query.def[0] = "Dinner Rolls";
query.def[1] = "item";
query.def[2] = "item";
query.def[3] = "price";
```

and

```
query.def["what"] = "Dinner Rolls";
query.def["wheref"] = "item";
query.def["field1"] = "item";
query.def["field2"] = "price";
```

Once all the parameters are set simply execute as you would have executed the query before you knew about template queries:

```
Result res = query.store()
```

4.4. Combining the two

You can also combine the use of setting the parameters at execution time and setting them via the def object by calling `Query::store()` (or `use()` or `execute()`) without passing the full number of parameters that the template supports:

```
query.def["field1"] = "item";
query.def["field2"] = "price";
Result res1 = query.store("Hamburger Buns", "item");
Result res2 = query.store(1.25, "price");
```

Would store the query:

```
select (item, price) from stock where item = "Hamburger Buns"
```

for res1 and

```
select (item, price) from stock where price = 1.25
```

for res2.

Now you see why we ordered the placeholders in the template above as we did: we used positions 0 and 1 for the ones we want to change frequently, and used 2 and 3 for the parameters that seldom change.

One thing to watch out for, however, is that `Query::store(const char* q)` is also defined for executing the query `q`. Therefore, when you call `Query::store()` (or `use()`, or `execute()`) with only one item and that item is a `const char*`, you need to explicitly convert it into a `SQLString` to get the right overload:

```
Result res = query.store(SQLString("Hamburger Buns"));
```

4.5. Error Handling

If for some reason you did not specify all the parameters when executing the query and the remaining parameters do not have their values set via def, the query object will throw a `SQLQueryNEParams` [[../refman/html/classmysqlpp_1_1SQLQueryNEParams.html](http://refman/html/classmysqlpp_1_1SQLQueryNEParams.html)] object. If this happens, you can get an explanation of what happened by checking the value of `SQLQueryNEParams::string`, like so:

```
query.def["field1"] = "item";
query.def["field2"] = "price";
Result res = query.store(1.25);
```

This would throw `SQLQueryNEParams` because the wheref is not specified.

In theory, this exception should never be thrown. If the exception is thrown it probably a logic error in your program.

5. Specialized SQL Structures

The Specialized SQL Structure (SSQLS) feature lets you easily define C++ structures that match the form of your SQL tables. Because of the extra functionality that this feature builds into these structures, MySQL++ can populate them automatically when retrieving data from the database; with queries returning many records, you can ask MySQL++ to populate an STL container of your SSQLS records with the results. When updating the database,

MySQL++ can use SSQLS structures to match existing data, and it can insert SSQLS structures directly into the database.

You define an SSQLS using one of several macros. (These are in the file `custom.h`, and in the file that it includes, `custom-macros.h`.) There are a bunch of different macros, for different purposes. The following sections will discuss each macro type separately, beginning with the easiest and most generally useful.

5.1. `sql_create`

This is the most basic sort of SSQLS declaration:

```
sql_create_5(stock, 0, 0,
             string, item,
             int, num,
             double, weight,
             double, price,
             mysqlpp::Date, date)
```

This creates a C++ structure called 'stock' containing five member variables, along with some constructors and other member functions useful with MySQL++.

One of the generated constructors takes a reference to a `mysqlpp::Row` object, allowing you to easily populate a vector of stocks like so:

```
vector<stock> result;
query.storein(result);
```

That's all there is to it. The only requirements are that the table structure be compatible with the SSQLS's member variables, and that the fields are in the same order.

The general format of this set of macros is:

```
sql_create_#(NAME, KEYS, INITPARMS, TYPE1, ITEM1, ... TYPE#, ITEM#)
```

Where # is the number of member variables, NAME is the name of the structure you wish to create, TYPE_x is the type name for a member variable, and ITEM_x is that variable's name.

The KEYS and INITPARMS arguments can always be zero, to keep things simple. We will discuss what happens if you use different values in the next few sections.

5.2. `sql_create` with Compare

SSQLS structures can also have member functions that allow you to compare one structure to another. You simply change the first 0 in the previous example (KEYS) to a higher value. If this number is N, then two structures are considered equal if the first N members of each are equal.

For example:

```
sql_create_5(stock, 1, 0,
             string, item,
             int, num,
             double, weight,
             double, price,
             mysqlpp::Date, date)
```

Here we are saying that the 'item' field is a kind of key field: it is always unique between any two 'stock' items, so if two stock records have equal item values, they are the same stock item.

That change adds the following members to the SSQLS:

```
struct stock {
    ...
    stock(const std::string &pl);
    set(const std::string &pl);
    bool operator == (const stock &other) const;
    bool operator != (const stock &other) const;
    bool operator > (const stock &other) const;
    bool operator < (const stock &other) const;
    bool operator >= (const stock &other) const;
    bool operator <= (const stock &other) const;
    int cmp (const stock &other) const;
    int compare (const stock &other) const;
}

int compare (const stock &x, const stock &y);
```

The global `compare()` function compares `x` to `y` and returns `<0` if `x < y`, `0` if `x = y`, and `>0` if `x > y`. `stock::cmp()` and `stock::compare()` are the same thing as `compare(*this, other)`.

The additional constructor initializes the key fields of the structure and leaves the other member variables undefined. This is useful for creating temporary objects to use for comparisons like `x <= stock("Hotdog")`.

Because `stock` is now less-than-comparable you can store the query results in an STL associative container:

```
std::set<stock> result;
query.storein(result);
```

And you can now use it like any other set:

```
cout << result.lower_bound(stock("Hamburger"))->item << endl;
```

This will return the first item that begins with "Hamburger".

You can also use it will any STL algorithm that require the values to be less-than-comparable.

5.3. `sql_create` with Additional Initializers

If third parameter for this macro (`INITPARMS`) is nonzero, the SSQLS will have two additional members functions that make it easier to initialize the structure's data members. For example:

```
sql_create_5(stock, 1, 5,
            string, item,
            int, num,
            double, weight,
            double, price,
            mysqlpp::Date, date)
```

will add these functions to the structure relative to that in the previous example:

```
struct stock {
    ...
    stock(const string&, const int&, const double&,
          const double&, const mysqlpp::Date&);
    set(const string&, const int&, const double&,
        const double&, const mysqlpp::Date&);
}
```

There is one trick with this: because each SSQLS has at least one other constructor besides the one defined by this feature, not every logical value for `INITPARMS` results in working code. A simple example is setting `KEYS` and

INITPARMS to the same value: you get two identical constructor definitions, so the compiler refuses to compile the code. If you are getting compiler errors having to do with duplicate definitions, try changing this value to zero.

5.4. Additional Features of Specialized SQL Structures

Up to this point, we haven't been using all of the features in the SSQLS structures we've been generating. We could have used the `sql_create_basic_*` macros instead, which would have worked just as well for what we've seen so far, and the generated code would have been smaller.

Why is it worth ignoring the "basic" variants of these macros, then? Consider this:

```
query.insert(s);
```

this does exactly what you think it does: it inserts 's' into the database. this is possible because a standard ssqsls has functions that the query object can call to get the list of fields and such, which it uses to build an insert query. `query::update()` and `query::replace()` also rely on this ssqsls feature. a basic ssqsls lacks these functions.

another feature of standard ssqslses you might find a use for is changing the table name used in queries. by default, the table in the mysql database is assumed to have the same name as the ssqsls structure type. but if this is inconvenient, you can globally change the table name used in queries like this:

```
stock::table() = "mystockdata";
```

at this point, we've seen all the major aspects of the ssqsls feature. the following sections look at some alternate methods for constructing ssqslses.

5.5. alternate creation methods

if for some reason you want your ssqsls data members to have different names than used in the mysql database, you can do so like this:

```
sql_create_c_names_5(stock, 1, 5,
    string, item, "item",
    int, num, "quantity",
    double, weight, "weight",
    double, price, "price"
    mysqlpp::Date, date, "shipment")
```

If you want your SSQSLs to have its data members in a different order from those in the MySQL table, you can do it like this:

```
sql_create_c_order_5(stock, 2, 5,
    mysqlpp::Date, date, 5,
    double, price, 4,
    string, item, 1,
    int, num, 2,
    double, weight, 3)
```

You can combine the custom names and custom ordering like this:

```
sql_create_complete_5(stock, 2, 5,
    mysqlpp::date, date, "shipment", 5,
    double, price, "price", 4,
    string, item, "item", 1,
    int, num, "quantity", 2,
    double, weight, "weight", 3)
```

all three of these macro types have "basic" variants that work the same way. again, basic ssqslses lack the features ne-

cessary for automatic insert, update and replace query creation.

5.6. expanding ssqls macros

if you ever need to see the code that a given ssqls declaration expands out to, use the utility `doc/ssqls-pretty`, like so:

```
ssqls-pretty < myprog.cpp |less
```

This locates the first SSQSL declaration in that file and uses the C++ preprocessor to expand that macro. You may have to change the script to tell it where your MySQL++ header files are.

5.7. Extending the SSQSL Mechanism

The SSQSL headers — `custom.h` and `custom-macros.h` — are automatically generated by the Perl script `custom.pl`. Although it is possible to change this script to get additional functionality, it's usually better to do that through inheritance.

A regular user may find it helpful to change the the limit on the maximum number of SSQSL data members allowed. It's 25 out of the box. A smaller value may speed up compile time, or you may require a higher value because you have more complex tables than that. Simply change the `max_data_members` variable at the top of `custom.pl` and say 'make'. The limit for Visual C++ is 31, according to one report. There doesn't seem to be a practical limit with GCC 3.3 at least: I set the limit to 100 and the only thing that happened is that `custom-macros.h` went from 1.3 MB to 18 MB and the build time for `examples/custom.*` got a lot longer.

6. Licensing

The primary copyright holders on MySQL++ are Kevin Atkinson (1998), MySQL AB (1999 through 2001) and Educational Technology Resources, Inc. (2004 through the date of this writing). This library is released under the GNU Lesser General Public License (LGPL), so all other contributions are also under the LGPL.

6.1. GNU Lesser General Public License

Version 2.1, February 1999

Copyright (C) 1991, 1999 Free Software Foundation, Inc. 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

[This is the first released version of the Lesser GPL. It also counts as the successor of the GNU Library Public License, version 2, hence the version number 2.1.]

Preamble

The licenses for most software are designed to take away your freedom to share and change it. By contrast, the GNU General Public Licenses are intended to guarantee your freedom to share and change free software--to make sure the software is free for all its users.

This license, the Lesser General Public License, applies to some specially designated software packages--typically libraries--of the Free Software Foundation and other authors who decide to use it. You can use it too, but we suggest you first think carefully about whether this license or the ordinary General Public License is the better strategy to use in any particular case, based on the explanations below.

When we speak of free software, we are referring to freedom of use, not price. Our General Public Licenses are designed to make sure that you have the freedom to distribute copies of free software (and charge for this service if you wish); that you receive source code or can get it if you want it; that you can change the software and use pieces of it in new free programs; and that you are informed that you can do these things.

To protect your rights, we need to make restrictions that forbid distributors to deny you these rights or to ask you to surrender these rights. These restrictions translate to certain responsibilities for you if you distribute copies of the library or if you modify it.

For example, if you distribute copies of the library, whether gratis or for a fee, you must give the recipients all the rights that we gave you. You must make sure that they, too, receive or can get the source code. If you link other code with the library, you must provide complete object files to the recipients, so that they can relink them with the library after making changes to the library and recompiling it. And you must show them these terms so they know their rights.

We protect your rights with a two-step method: (1) we copyright the library, and (2) we offer you this license, which gives you legal permission to copy, distribute and/or modify the library.

To protect each distributor, we want to make it very clear that there is no warranty for the free library. Also, if the library is modified by someone else and passed on, the recipients should know that what they have is not the original version, so that the original author's reputation will not be affected by problems that might be introduced by others.

Finally, software patents pose a constant threat to the existence of any free program. We wish to make sure that a company cannot effectively restrict the users of a free program by obtaining a restrictive license from a patent holder. Therefore, we insist that any patent license obtained for a version of the library must be consistent with the full freedom of use specified in this license.

Most GNU software, including some libraries, is covered by the ordinary GNU General Public License. This license, the GNU Lesser General Public License, applies to certain designated libraries, and is quite different from the ordinary General Public License. We use this license for certain libraries in order to permit linking those libraries into non-free programs.

When a program is linked with a library, whether statically or using a shared library, the combination of the two is legally speaking a combined work, a derivative of the original library. The ordinary General Public License therefore permits such linking only if the entire combination fits its criteria of freedom. The Lesser General Public License permits more lax criteria for linking other code with the library.

We call this license the "Lesser" General Public License because it does Less to protect the user's freedom than the ordinary General Public License. It also provides other free software developers Less of an advantage over competing non-free programs. These disadvantages are the reason we use the ordinary General Public License for many libraries. However, the Lesser license provides advantages in certain special circumstances.

For example, on rare occasions, there may be a special need to encourage the widest possible use of a certain library, so that it becomes a de-facto standard. To achieve this, non-free programs must be allowed to use the library. A more frequent case is that a free library does the same job as widely used non-free libraries. In this case, there is little to gain by limiting the free library to free software only, so we use the Lesser General Public License.

In other cases, permission to use a particular library in non-free programs enables a greater number of people to use a large body of free software. For example, permission to use the GNU C Library in non-free programs enables many more people to use the whole GNU operating system, as well as its variant, the GNU/Linux operating system.

Although the Lesser General Public License is Less protective of the users' freedom, it does ensure that the user of a program that is linked with the Library has the freedom and the wherewithal to run that program using a modified version of the Library.

The precise terms and conditions for copying, distribution and modification follow. Pay close attention to the difference between a "work based on the library" and a "work that uses the library". The former contains code derived from the library, whereas the latter must be combined with the library in order to run.

GNU LESSER GENERAL PUBLIC LICENSE

TERMS AND CONDITIONS FOR COPYING, DISTRIBUTION AND MODIFICATION

0. This License Agreement applies to any software library or other program which contains a notice placed by the

copyright holder or other authorized party saying it may be distributed under the terms of this Lesser General Public License (also called "this License"). Each licensee is addressed as "you".

A "library" means a collection of software functions and/or data prepared so as to be conveniently linked with application programs (which use some of those functions and data) to form executables.

The "Library", below, refers to any such software library or work which has been distributed under these terms. A "work based on the Library" means either the Library or any derivative work under copyright law: that is to say, a work containing the Library or a portion of it, either verbatim or with modifications and/or translated straightforwardly into another language. (Hereinafter, translation is included without limitation in the term "modification".)

"Source code" for a work means the preferred form of the work for making modifications to it. For a library, complete source code means all the source code for all modules it contains, plus any associated interface definition files, plus the scripts used to control compilation and installation of the library.

Activities other than copying, distribution and modification are not covered by this License; they are outside its scope. The act of running a program using the Library is not restricted, and output from such a program is covered only if its contents constitute a work based on the Library (independent of the use of the Library in a tool for writing it). Whether that is true depends on what the Library does and what the program that uses the Library does.

1. You may copy and distribute verbatim copies of the Library's complete source code as you receive it, in any medium, provided that you conspicuously and appropriately publish on each copy an appropriate copyright notice and disclaimer of warranty; keep intact all the notices that refer to this License and to the absence of any warranty; and distribute a copy of this License along with the Library.

You may charge a fee for the physical act of transferring a copy, and you may at your option offer warranty protection in exchange for a fee.

2. You may modify your copy or copies of the Library or any portion of it, thus forming a work based on the Library, and copy and distribute such modifications or work under the terms of Section 1 above, provided that you also meet all of these conditions:

- a) The modified work must itself be a software library.
- b) You must cause the files modified to carry prominent notices stating that you changed the files and the date of any change.
- c) You must cause the whole of the work to be licensed at no charge to all third parties under the terms of this License.
- d) If a facility in the modified Library refers to a function or a table of data to be supplied by an application program that uses the facility, other than as an argument passed when the facility is invoked, then you must make a good faith effort to ensure that, in the event an application does not supply such function or table, the facility still operates, and performs whatever part of its purpose remains meaningful.

(For example, a function in a library to compute square roots has a purpose that is entirely well-defined independent of the application. Therefore, Subsection 2d requires that any application-supplied function or table used by this function must be optional: if the application does not supply it, the square root function must still compute square roots.)

These requirements apply to the modified work as a whole. If identifiable sections of that work are not derived from the Library, and can be reasonably considered independent and separate works in themselves, then this License, and its terms, do not apply to those sections when you distribute them as separate works. But when you distribute the same sections as part of a whole which is a work based on the Library, the distribution of the whole must be on the terms of this License, whose permissions for other licensees extend to the entire whole, and thus to each and every part regardless of who wrote it.

Thus, it is not the intent of this section to claim rights or contest your rights to work written entirely by you; rather, the intent is to exercise the right to control the distribution of derivative or collective works based on the Library.

In addition, mere aggregation of another work not based on the Library with the Library (or with a work based on the Library) on a volume of a storage or distribution medium does not bring the other work under the scope of this License.

3. You may opt to apply the terms of the ordinary GNU General Public License instead of this License to a given copy of the Library. To do this, you must alter all the notices that refer to this License, so that they refer to the ordinary GNU General Public License, version 2, instead of to this License. (If a newer version than version 2 of the ordinary GNU General Public License has appeared, then you can specify that version instead if you wish.) Do not make any other change in these notices.

Once this change is made in a given copy, it is irreversible for that copy, so the ordinary GNU General Public License applies to all subsequent copies and derivative works made from that copy.

This option is useful when you wish to copy part of the code of the Library into a program that is not a library.

4. You may copy and distribute the Library (or a portion or derivative of it, under Section 2) in object code or executable form under the terms of Sections 1 and 2 above provided that you accompany it with the complete corresponding machine-readable source code, which must be distributed under the terms of Sections 1 and 2 above on a medium customarily used for software interchange.

If distribution of object code is made by offering access to copy from a designated place, then offering equivalent access to copy the source code from the same place satisfies the requirement to distribute the source code, even though third parties are not compelled to copy the source along with the object code.

5. A program that contains no derivative of any portion of the Library, but is designed to work with the Library by being compiled or linked with it, is called a "work that uses the Library". Such a work, in isolation, is not a derivative work of the Library, and therefore falls outside the scope of this License.

However, linking a "work that uses the Library" with the Library creates an executable that is a derivative of the Library (because it contains portions of the Library), rather than a "work that uses the library". The executable is therefore covered by this License. Section 6 states terms for distribution of such executables.

When a "work that uses the Library" uses material from a header file that is part of the Library, the object code for the work may be a derivative work of the Library even though the source code is not. Whether this is true is especially significant if the work can be linked without the Library, or if the work is itself a library. The threshold for this to be true is not precisely defined by law.

If such an object file uses only numerical parameters, data structure layouts and accessors, and small macros and small inline functions (ten lines or less in length), then the use of the object file is unrestricted, regardless of whether it is legally a derivative work. (Executables containing this object code plus portions of the Library will still fall under Section 6.)

Otherwise, if the work is a derivative of the Library, you may distribute the object code for the work under the terms of Section 6. Any executables containing that work also fall under Section 6, whether or not they are linked directly with the Library itself.

6. As an exception to the Sections above, you may also combine or link a "work that uses the Library" with the Library to produce a work containing portions of the Library, and distribute that work under terms of your choice, provided that the terms permit modification of the work for the customer's own use and reverse engineering for debugging such modifications.

You must give prominent notice with each copy of the work that the Library is used in it and that the Library and its use are covered by this License. You must supply a copy of this License. If the work during execution displays copyright notices, you must include the copyright notice for the Library among them, as well as a reference directing the user to the copy of this License. Also, you must do one of these things:

- a) Accompany the work with the complete corresponding machine-readable source code for the Library including whatever changes were used in the work (which must be distributed under Sections 1 and 2 above); and, if the work is an executable linked with the Library, with the complete machine-readable "work that uses the Library", as object code and/or source code, so that the user can modify the Library and then relink to produce a modified executable containing the modified Library. (It is understood that the user who changes the contents of definitions files in the Library will not necessarily be able to recompile the application to use the modified definitions.)
- b) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (1) uses at run time a copy of the library already present on the user's computer system, rather than copying library functions into the executable, and (2) will operate properly with a modified version of the library, if the user installs one, as long as the modified version is interface-compatible with the version that the work was made with.
- c) Accompany the work with a written offer, valid for at least three years, to give the same user the materials specified in Subsection 6a, above, for a charge no more than the cost of performing this distribution.
- d) If distribution of the work is made by offering access to copy from a designated place, offer equivalent access to copy the above specified materials from the same place.
- e) Verify that the user has already received a copy of these materials or that you have already sent this user a copy.

For an executable, the required form of the "work that uses the Library" must include any data and utility programs needed for reproducing the executable from it. However, as a special exception, the materials to be distributed need not include anything that is normally distributed (in either source or binary form) with the major components (compiler, kernel, and so on) of the operating system on which the executable runs, unless that component itself accompanies the executable.

It may happen that this requirement contradicts the license restrictions of other proprietary libraries that do not normally accompany the operating system. Such a contradiction means you cannot use both them and the Library together in an executable that you distribute.

7. You may place library facilities that are a work based on the Library side-by-side in a single library together with other library facilities not covered by this License, and distribute such a combined library, provided that the separate distribution of the work based on the Library and of the other library facilities is otherwise permitted, and provided that you do these two things:

- a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities. This must be distributed under the terms of the Sections above.
- b) Give prominent notice with the combined library of the fact that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

8. You may not copy, modify, sublicense, link with, or distribute the Library except as expressly provided under this License. Any attempt otherwise to copy, modify, sublicense, link with, or distribute the Library is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

9. You are not required to accept this License, since you have not signed it. However, nothing else grants you permission to modify or distribute the Library or its derivative works. These actions are prohibited by law if you do not accept this License. Therefore, by modifying or distributing the Library (or any work based on the Library), you indicate your acceptance of this License to do so, and all its terms and conditions for copying, distributing or modifying the Library or works based on it.

10. Each time you redistribute the Library (or any work based on the Library), the recipient automatically receives a license from the original licensor to copy, distribute, link with or modify the Library subject to these terms and conditions. You may not impose any further restrictions on the recipients' exercise of the rights granted herein. You are not responsible for enforcing compliance by third parties with this License.

11. If, as a consequence of a court judgment or allegation of patent infringement or for any other reason (not limited to patent issues), conditions are imposed on you (whether by court order, agreement or otherwise) that contradict the conditions of this License, they do not excuse you from the conditions of this License. If you cannot distribute so as to satisfy simultaneously your obligations under this License and any other pertinent obligations, then as a consequence you may not distribute the Library at all. For example, if a patent license would not permit royalty-free redistribution of the Library by all those who receive copies directly or indirectly through you, then the only way you could satisfy both it and this License would be to refrain entirely from distribution of the Library.

If any portion of this section is held invalid or unenforceable under any particular circumstance, the balance of the section is intended to apply, and the section as a whole is intended to apply in other circumstances.

It is not the purpose of this section to induce you to infringe any patents or other property right claims or to contest validity of any such claims; this section has the sole purpose of protecting the integrity of the free software distribution system which is implemented by public license practices. Many people have made generous contributions to the wide range of software distributed through that system in reliance on consistent application of that system; it is up to the author/donor to decide if he or she is willing to distribute software through any other system and a licensee cannot impose that choice.

This section is intended to make thoroughly clear what is believed to be a consequence of the rest of this License.

12. If the distribution and/or use of the Library is restricted in certain countries either by patents or by copyrighted interfaces, the original copyright holder who places the Library under this License may add an explicit geographical distribution limitation excluding those countries, so that distribution is permitted only in or among countries not thus excluded. In such case, this License incorporates the limitation as if written in the body of this License.

13. The Free Software Foundation may publish revised and/or new versions of the Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library specifies a version number of this License which applies to it and "any later version", you have the option of following the terms and conditions either of that version or of any later version published by the Free Software Foundation. If the Library does not specify a license version number, you may choose any version ever published by the Free Software Foundation.

14. If you wish to incorporate parts of the Library into other free programs whose distribution conditions are incompatible with these, write to the author to ask for permission. For software which is copyrighted by the Free Software Foundation, write to the Free Software Foundation; we sometimes make exceptions for this. Our decision will be guided by the two goals of preserving the free status of all derivatives of our free software and of promoting the sharing and reuse of software generally.

NO WARRANTY

15. BECAUSE THE LIBRARY IS LICENSED FREE OF CHARGE, THERE IS NO WARRANTY FOR THE LIBRARY, TO THE EXTENT PERMITTED BY APPLICABLE LAW. EXCEPT WHEN OTHERWISE STATED IN WRITING THE COPYRIGHT HOLDERS AND/OR OTHER PARTIES PROVIDE THE LIBRARY "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE ENTIRE RISK AS TO THE QUALITY AND PERFORMANCE OF THE LIBRARY IS WITH YOU. SHOULD THE LIBRARY PROVE DEFECTIVE, YOU ASSUME THE COST OF ALL NECESSARY SERVICING, REPAIR OR CORRECTION.

16. IN NO EVENT UNLESS REQUIRED BY APPLICABLE LAW OR AGREED TO IN WRITING WILL ANY COPYRIGHT HOLDER, OR ANY OTHER PARTY WHO MAY MODIFY AND/OR REDISTRIBUTE THE LIB-

RARY AS PERMITTED ABOVE, BE LIABLE TO YOU FOR DAMAGES, INCLUDING ANY GENERAL, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OR INABILITY TO USE THE LIBRARY (INCLUDING BUT NOT LIMITED TO LOSS OF DATA OR DATA BEING RENDERED INACCURATE OR LOSSES SUSTAINED BY YOU OR THIRD PARTIES OR A FAILURE OF THE LIBRARY TO OPERATE WITH ANY OTHER SOFTWARE), EVEN IF SUCH HOLDER OR OTHER PARTY HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

END OF TERMS AND CONDITIONS

How to Apply These Terms to Your New Libraries

If you develop a new library, and you want it to be of the greatest possible use to the public, we recommend making it free software that everyone can redistribute and change. You can do so by permitting redistribution under these terms (or, alternatively, under the terms of the ordinary General Public License).

To apply these terms, attach the following notices to the library. It is safest to attach them to the start of each source file to most effectively convey the exclusion of warranty; and each file should have at least the "copyright" line and a pointer to where the full notice is found.

<one line to give the library's name and a brief idea of what it does.>

Copyright © <year> <name of author>

This library is free software; you can redistribute it and/or modify it under the terms of the GNU Lesser General Public License as published by the Free Software Foundation; either version 2.1 of the License, or (at your option) any later version.

This library is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU Lesser General Public License along with this library; if not, write to the Free Software Foundation, Inc., 59 Temple Place, Suite 330, Boston, MA 02111-1307 USA

Also add information on how to contact you by electronic and paper mail.

You should also get your employer (if you work as a programmer) or your school, if any, to sign a "copyright disclaimer" for the library, if necessary. Here is a sample; alter the names:

Yoyodyne, Inc., hereby disclaims all copyright interest in the library `Frob' (a library for tweaking knobs) written by James Random Hacker.

<signature of Ty Coon>, 1 April 1990

Ty Coon, President of Vice

That's all there is to it!